



TQX.11003 Triple QX Motor Oil 5W-30 SYNPLUS C2

Document version: 5 Sep 2026



Description

This TQX SYNPLUS C2 5W30 synthetic lubricant is based on special selected very high quality base oils of the latest generation plus an advanced additive package. It is designed to provide the highest fuel economy and lowest CO2 emissions.

According to the specifications of

ACEA C2
API CF / SN
ILSAC GF-5
PSA B71 2290 <2017
Renault RN 0700

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776052	1 L	12	-
TQX.521776051	5 L	4	-
TQX.521776055	20 L	1	-
TQX.521776059	60 L	1	6
TQX.521772006	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.850	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	66.8	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	11.8	mm ² /s	ASTM D445
Viscosity Index	171		ASTM D2270
Flashpoint COC	226	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	6.8	mgKOH/g	ASTM D2896
Sulphated Ash	0.78	mass%	ASTM D874