



TQX.11004 Triple QX Motor Oil 5W-30 SYNPLUS C3

Document version: 8 Sep 2026



Description	This TQX SYNPLUS C3 5W30 mid-SAPS synthetic lubricant meets the specifications of different OEM-s. The combination of excellent low viscosity properties and highly protective additives enable the engine to run with higher fuel efficiency.			
According to the specifications of	ACEA C3 API CF / SN BMW Longlife-04 GM dexos 2 MB 229.51 / 229.52 Opel OV 040 1547 - D30 VW 505.00 / 505.01			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776062	1 L	12	-
	TQX.521776061	5 L	4	-
	TQX.521776065	20 L	1	-
	TQX.521776069	60 L	1	-
	TQX.521772016	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.850	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	67.5	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	11.8	mm2/s	ASTM D445
Viscosity Index	172		ASTM D2270
Flashpoint COC	232	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	7.0	mgKOH/g	ASTM D2896
Sulphated Ash	0.79	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.